

Aarhus



RWY day marking 10R / 28L : THR, RWY NR, TDZ, Centre line, Edge.
10L / 28R : THR, RWY NR, Aiming point, TDZ, Centre line.

Lighting RWY 10R/ 28L : PAPI, ALS, THR, TDZ 28L, Centre line, Edge, SWY, End.
Lighting RWY 10L / 28R : THR, Edge, End.
Secondary power supply : Yes, switch-over time MAX 15 SEC.
All OBST are marked by day and night.

Width : A, B, E, T, W, Y, Z : 23 M. G : 10 M.
Pavement : A, B, E, G, W, Y, Z : Asphalt. T : Asphalt / Concrete.
Strength : E, W, Y : PCN 120 / F / B / W / T. A, B : PCN 76 / F / B / X / U. T : PCN 76 / R / B / X / T.
Z : PCN 76 / R / B / X / U. G : 76 / R / B / X / U.

Day marking : Centre line, Holding position.
Lighting : Blue edge LIL, RGL for RWY 10R / 28L at holding PSN TWY Z, Y, E and T, and RWY 10L / 28R north of RWY at holding PSN TWY E and W.
Centre line green / yellow on TWY E.
Taxiing guidance system : Sign boards.

All RWY slopes : Less than 0.07 %.