

AD 3.3 AITOLOAKARNANIA / ASTAKOS - PLATIGIALI**AD 3.3.1 HELIPORT NAME AND INDICATORS**

1. Location Indicator	2. Name	3. Grouping Indicator
NIL	AITOLOAKARNANIA / ASTAKOS - PLATIGIALI	P/HEL

AD 3.3.2 HELIPORT GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Heliport reference point coordinates and site at heliport	382854.00 N 210551.00 E, geometric centre of TLOF
2	Direction and distance from (city)	At location NA.VI.PE, Platigiali port, 10 km East of Astakos city.
3	Elevation/Reference temperature	50 M (164 FT)/ NIL
4	Geoid undulation at ELEV PSN	NIL
5	MAG VAR/Annual change	3°19'E (3.32°E) (JAN 2010) / 4.60°E (0.0767°E) increasing
6	Heliport Administration, address, telephone, telefax, telex, AFS	AKARPORT S.A. Platigiali GR 30006 Astakos, Aitoloakarnania TEL: +30 26310 22600, +30 26310 56000 FAX: +30 26310 27526 E-MAIL: koloniasd@akarport.com ; stathopc@akarport.com
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	PPR by the owner. Supervised by CAA

AD 3.3.3 OPERATIONAL HOURS

1	Heliport Administration	HX
12	Remarks	HX: daily hours O/R

AD 3.3.4 HANDLING SERVICES AND FACILITIES

NIL

AD 3.3.5 PASSENGER FACILITIES

NIL

AD 3.3.6 RESCUE AND FIRE FIGHTING SERVICES

1	Heliport category for fire fighting	H2
4	Remarks	NIL

AD 3.3.7 SEASONAL AVAILABILITY - CLEARING

NIL

AD 3.3.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

NIL

AD 3.3.9 MARKINGS AND MARKERS

1	Final approach and take-off markings	Heliport identification (H), TLOF edge, TDZ marking
2	TWY, air TWY, air transit route markers	NIL
3	Remarks	NIL

AD 3.3.10 HELIPORT OBSTACLES

In Area 2					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

In Area 3					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

AD 3.3.11 METEOROLOGICAL INFORMATION PROVIDED

NIL

AD 3.3.12 HELIPORT DATA

1	Heliport type	Surface level
2	TLOF dimensions	24 M in diameter
3	FATO, GEO bearings	050° / 230° GEO
4	FATO dimensions and SFC type	24 M in diameter concrete
5	TLOF, SFC and BRG strength	concrete
6	Coordinates of geometric centre TLOF or THR of FATO and geoid undulation	TLOF: 382854.00N 0210551.00E / NIL
7	TLOF/FATO, elevation and slope	TLOF: 50 M (164 FT) / NIL
8	Safety area dimensions	4 M width
9	HEL CWY dimensions	NIL
10	Obstacle free sector	NIL
11	Remarks	To be used by helicopters with maximum length 16 M.

AD 3.3.13 DECLARED DISTANCES

NIL

AD 3.3.14 APPROACH AND FATO LIGHTING

2	Type of visual approach slope indicator system	NIL
5	TLOF LGT system characteristics and location	NIL
6	Remarks	NIL

AD 3.3.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Heliport BCN location and characteristics Hours of operation	NIL
2	WDI location and LGT	lighted
4	Secondary power supply/switch-over time	NIL
5	Remarks	NIL

AD 3.3.16 ATS AIRSPACE

NIL

AD 3.3.17 ATS COMMUNICATION FACILITIES

NIL

AD 3.3.18 ATS RADIO NAVIGATION AND LANDING AIDS

NIL

AD 3.3.19 LOCAL TRAFFIC REGULATIONS**3.3.19.1 Heliport regulations**

3.3.19.1.1 The heliport will be used exclusively for the needs of the company AKARPORT S.A. as well as for the needs of persons who have obtained the permission of the owner, without fee.

AD 3.3.20 NOISE ABATEMENT PROCEDURES

3.3.20.1 NIL

AD 3.3.21 FLIGHT PROCEDURES**3.3.21.1 GENERAL**

3.3.21.1.1 NIL

AD 3.3.22 ADDITIONAL INFORMATION

3.3.22.1 NIL

AD 3.3.23 CHARTS RELATED TO THE HELIPORT

NIL