

AD 3.70 ATTIKI / KOROPI MPOTA-PROFARTA**AD 3.70.1 HELIPORT NAME AND INDICATORS**

1. Location Indicator	2. Name	3. Grouping Indicator
NIL	ATTIKI / KOROPI MPOTA-PROFARTA	P/HEL

AD 3.70.2 HELIPORT GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Heliport reference point coordinates and site at heliport	375211N 0235238E, geometric centre of FATO
2	Direction and distance from (city)	At location "Mpota – Profarta", Koropi.
3	Elevation/Reference temperature	163 M (534.78 FT) / NIL
4	Geoid undulation at ELEV PSN	NIL
5	MAG VAR/Annual change	NIL / NIL
6	Heliport Administration, address, telephone, telefax, telex, AFS	GREEK AIR S.A 81, Archimidous str. GR 19400 Koropi, Attiki TEL: +30 210 6020609 FAX: +30 210 6627060
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	PPR by the owner. Supervised by CAA

AD 3.70.3 OPERATIONAL HOURS

1	Heliport Administration	HX
2	Remarks	HX: daily hours O/R

AD 3.70.4 HANDLING SERVICES AND FACILITIES

NIL

AD 3.70.5 PASSENGER FACILITIES

NIL

AD 3.70.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	H2
2	Remarks	NIL

AD 3.70.7 SEASONAL AVAILABILITY - CLEARING

NIL

AD 3.70.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

NIL

AD 3.70.9 MARKINGS AND MARKERS

1	Final approach and take-off markings	Heliport identification (H), TLOF edge, TDZ marking.
2	TWY, air TWY, air transit route markers	NIL
3	Remarks	NIL

AD 3.70.10 HELIPORT OBSTACLES

In Area 2					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

In Area 3					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

AD 3.70.11 METEOROLOGICAL INFORMATION PROVIDED

NIL

AD 3.70.12 HELIPORT DATA

1	Heliport type	Surface level
2	TLOF dimensions	18 M in diameter
3	FATO, GEO bearings	135° / 355° GEO
4	FATO dimensions and SFC type	18 M in diameter, concrete
5	TLOF, SFC and BRG strength	concrete
6	Coordinates of geometric centre TLOF or THR of FATO and geoid undulation	TLOF: 375212.06N 0235227.27E / NIL
7	TLOF/FATO, elevation and slope	TLOF: 163 M (534.78 FT) / NIL
8	Safety area dimensions	9 M width
9	HEL CWY dimensions	NIL
10	Obstacle free sector	NIL
11	Remarks	To be used by helicopters with maximum length 18 M.

AD 3.70.13 DECLARED DISTANCES

NIL

AD 3.70.14 APPROACH AND FATO LIGHTING

2	Type of visual approach slope indicator system	NIL
5	TLOF LGT system characteristics and location	NIL
6	Remarks	NIL

AD 3.70.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Heliport BCN location and characteristics Hours of operation	NIL
2	WDI location and LGT	Not lighted
4	Secondary power supply/switch-over time	NIL
5	Remarks	NIL

AD 3.70.16 ATS AIRSPACE

See LGAV AD 2.17.

AD 3.70.17 ATS COMMUNICATION FACILITIES

NIL

AD 3.70.18 ATS RADIO NAVIGATION AND LANDING AIDS

NIL

AD 3.70.19 LOCAL TRAFFIC REGULATIONS**3.70.19.1 Heliport regulations**

3.70.19.1.1 The heliport will be used exclusively for the needs of the company GREEK AIR S.A. as well as for the needs of persons who have obtained the permission of the owner.

AD 3.70.20 NOISE ABATEMENT PROCEDURES

NIL

AD 3.70.21 FLIGHT PROCEDURES**3.70.21.1 General**

3.70.21.1.1 Heliport is located within ATHINAI TMA (see **ENR 2.1**) and within ATHINAI ELEFThERIOS VENIZELOS CTR.

3.70.21.1.2 Heliport can be used only during day time and under VMC conditions.

3.70.21.1.3 Helicopters shall only use the following compulsory reporting points:

REPORTING POINTS	ALTITUDE (AMSL)	COORDINATES
DAMARI	1000FT	375323N 0235027E
THORIKO KALYVIA	1000FT	375036N 0235502E
AGIOS THOMAS	1500FT	375726N 0235344E
STAVROS	Outbound 2500FT – Inbound 2000FT	380039N 0235039E
NORTH MAKROS	1500FT	374521N 0240841E
ABEAM PATROKLOS	1000FT	373808N 0235551E
VILIZA (West Test Flight area)	1000FT	375506N 0234946E
KINETIZA MONASTERY (East Test Flight area)	1000FT	375025N 0235713E
KEA	1500FT	373103N 0241718E

3.70.21.1.4 Outbound traffic

3.70.21.1.4.1 Prior communication with Start-up-Delivery Tower Controller (frequency 118.675 MHz) is required for departing helicopters. The clearance will be issued depending on traffic density. Pilots will receive instructions regarding the transponder settings, latest QNH, the outbound route to be expected and the ATC unit to be conducted with the associated frequency. ATC may apply temporary suspension measures when it deems necessary due to operational reasons.

3.70.21.1.5 Inbound traffic

3.70.21.1.5.1 Pilots intending to land to the heliport, shall be instructed by ATH TMA INFO (frequency 124.025 MHz) to contact LGAV VENIZELOS TOWER frequency 118.625 over THORIKO KALYVIA or frequency 136.275 over STAVROS.

3.70.21.1.6 Pilots of helicopters shall cross without delay the ILS of the runways, not above 700 FT, leaving the area free immediately and shall strictly adhere to ATC instructions to avoid unacceptable ATC workload and delays.

3.70.21.1.7 IFR traffic shall have priority over VFR traffic. A continuous two-way communication with the appropriate ATS authority is required.

3.70.21.1.8 Caution is advised, TCAS alerts due to the proximity of heliport to threshold of runways 03L/03R LGAV.

3.70.21.1.9 Simultaneous movements from to heliports of KOROPi PROFARTA and KOROPi MPOTA-PROFARTA are not allowed due to their proximity.

3.70.21.1.10 Helicopter flights to and from the heliport shall be conducted according to the ATS Rules and follow the appropriate VFR Routes and altitudes within ATHINAI TMA (see **ENR 1.2**, as well as **LGAV AD 2.22** and relevant charts in **LGAV AD 2.24**).

AD 3.70.22 ADDITIONAL INFORMATION

NIL

AD 3.70.23 CHARTS RELATED TO THE HELIPORT

NIL