

LGKS AD 2.1 AERODROME LOCATION INDICATOR AND NAME
LGKS – KASSOS**LGKS AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA**

1	ARP coordinates and site at AD	352517N 0265436E Centre of RWY 09/27
2	Direction and distance from (city)	BRG: NIL, 0.27 NM (500 M) NW of the village.
3	Elevation/Reference temperature	10.73 M (35.20 FT) / 29°C
4	Geoid undulation at AD ELEV PSN	NIL
5	MAG VAR/Annual change	5°E (JAN 2024) / 5'30"E
6	AD Administration, address, telephone, telefax, telex, AFS	Hellenic Aviation Service Provider (HASP) Kassos Airport GR 85800, KASSOS TEL: +30 22450 41587 FAX: +30 22450 42722 AFTN: LGKSYDYX
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	NIL

LGKS AD 2.3 OPERATIONAL HOURS

1	AD Administration	HO
2	Customs and immigration	NIL
3	Health and sanitation	NIL
4	AIS Briefing Office	HO
5	ATS Reporting Office (ARO)	HO (TEL: +30 22450 41587)
6	MET Briefing Office	HO (MET)
7	ATS	HO
8	Fuelling	NIL
9	Handling	NIL
10	Security	HO
11	De-icing	NIL
12	Remarks	NIL

LGKS AD 2.4 HANDLING SERVICES AND FACILITIES

1	Cargo-handling facilities	NIL
2	Fuel/oil types	Fuel: NIL Oil: NIL
3	Fuelling facilities/capacity	NIL
4	De-icing facilities	NIL
5	Hangar space for visiting aircraft	NIL
6	Repair facilities for visiting aircraft	NIL
7	Remarks	NIL

LGKS AD 2.5 PASSENGER FACILITIES

1	Hotels	At the village.
2	Restaurants	At the village.
3	Transportation	Taxi.
4	Medical facilities	NIL
5	Bank and Post Office	NIL
6	Tourist Office	NIL
7	Remarks	NIL

LGKS AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	CIV CAT: 4
2	Rescue equipment	Equivalent for CAT 4 requirements.
3	Capability for removal of disabled aircraft	NIL
4	Remarks	First 250 M of RWY 27 are visible only from AFIS site.

LGKS AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	Types of clearing equipment	NIL
2	Clearance priorities	NIL
3	Remarks	All seasons.

LGKS AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	Apron surface and strength	Surface: Asphalt Strength: NIL
2	Taxiway designation, width, surface and strength	Width: NIL Surface: Asphalt Strength: NIL
3	Altimeter checkpoint location and elevation	NIL
4	VOR checkpoints	NIL
5	INS checkpoints	NIL
6	Remarks	Parking area 50 × 30 M.

LGKS AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands	Guidance to stands by Marshaller.
2	RWY and TWY markings and LGT	LGT: RWY: Threshold, end, edge. TWY: Edge. Markings: RWY: Center line, Thresholds, Touch down zone. TWY: NIL
3	Stop bars	NIL
4	Remarks	NIL

LGKS AD 2.10 AERODROME OBSTACLES

In approach/TKOF areas			In circling area and at AD		Remarks
1			2		3
RWY NR/ Area affected	Obstacle type Elevation Markings/LGT	Coordinates	Obstacle type Elevation Markings/LGT	Coordinates	
a	b	c	a	b	
09	See relevant LGKS AOC chart-ICAO				NIL
27	See relevant LGKS AOC chart-ICAO				

LGKS AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	Associated MET Office	KASSOS / III
2	Hours of service MET Office outside hours	HO NATIONAL METEOROLOGICAL CENTRE ATHINAI
3	Office responsible for TAF preparation Periods of validity	NATIONAL METEOROLOGICAL CENTRE ATHINAI 9HR
4	Trend forecast interval of issuance	NO TREND

5	Briefing/consultation provided	Personal consultation. Telephone.
6	Flight documentation Language(s) used	Tabular forms Greek, English
7	Charts and other information available for briefing or consultation	SWH, SWL, W, T, MW
8	Supplementary equipment available for providing information	Online data connection to the data Bank of the Hellenic National Meteorological Service has been established.
9	ATS units provided with information	KASSOS AFIS.
10	Additional information (limitation of service, etc.)	All data over FL100 are issued by World Area Forecast Centres. TEL: +30 22450 41590, +30 6983526333.

LGKS AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	TRUE BRG	Dimensions of RWY (M)	Strength (PCN) and surface of RWY and SWY	THR coordinates RWY end coordinates THR geoid undulation	THR elevation and highest elevation of TDZ of precision APP RWY
1	2	3	4	5	6
09	092°	983 × 25	NIL Asphalt	352517.50N 0265416.53E	THR 6.01 M / 19.71 FT TDZ: NIL
27	272°	983 × 25	NIL Asphalt	352516.17N 0265455.41E	THR 7.52 M / 24.67 FT TDZ: NIL

Designations RWY NR	Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)	OFZ	Remarks
1	7	8	9	10	11	12	13
09	NIL	NIL	NIL	NIL	NIL	NIL	See also LGKS AD and AOC chart- ICAO.
27	NIL	NIL	NIL	NIL	NIL	NIL	First 380 M of RWY 09 not visible from AFIS site.

LGKS AD 2.13 DECLARED DISTANCES

RWY Designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Remarks
1	2	3	4	5	6
09	982	982	982	982	NIL
27	982	982	982	982	NIL

LGKS AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	APCH LGT Type Length Intensity	THR LGT Colour Wingbars	PAPI VASIS Angle (MEHT)	TDZ, LGT Length	RWY Centre-line LGT Length Spacing, Colour Intensity	RWY edge LGT Length Spacing Colour Intensity	RWY End LGT Colour Wingbars	SWY LGT Length Colour	Remarks
1	2	3	4	5	6	7	8	9	10
09	NIL	Yes	NIL	NIL	NIL	Yes	Yes	NIL	See LGKS AD chart-ICAO.
27	NIL	Yes	NIL	NIL	NIL	Yes	Yes	NIL	

LGKS AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	ABN/IBN location, characteristics and operational hours	ABN: NIL IBN: NIL
2	LDI location and LGT Anemometer location and LGT	LDI: NIL WDI: 2 WDI Anemometer: NIL.
3	TWY edge and centre line lighting	Edge: Blue
4	Secondary power supply/switch-over time	Available
5	Remarks	Apron: Flood lights.

LGKS AD 2.16 HELICOPTER LANDING AREA

1	Coordinates TLOF or THR of FATO Geoid undulation	NIL
2	TLOF and/or FATO elevation M/FT	NIL
3	TLOF and FATO area dimensions, surface, strength, marking	NIL
4	True BRG of FATO	NIL
5	Declared distance available	NIL
6	APP and FATO lighting	NIL
7	Remarks	See LGKS AD 2.20.4

LGKS AD 2.17 ATS AIRSPACE

1	Designation and lateral limits	KASSOS ATZ: Circle, 5 NM radius centred at 352517N 0265436E.
2	Vertical limits	ATZ: SFC to 2000 FT ALT.
3	Airspace classification	Class G
4	ATS unit call sign Language(s)	ATZ: KASSOS INFORMATION Greek, English.
5	Transition altitude	NIL
6	Remarks	NIL

LGKS AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	Call sign	Frequency/ VHF CH	Operational hours	Remarks
1	2	3	4	5
AFIS	KASSOS INFORMATION	124.175	HO	Primary freq. Coverage FL 030 / 15 NM.
G/A/G	KASSOS RADIO	5637 kHz 2989 kHz	HO: 0400 – 1700 HO: 1700 – 0400	Primary freq. Primary freq.
All ATS Communication Facilities under responsibility of HASP.				

LGKS AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid MAG VAR CAT of ILS/MLS (For VOR/ILS/MLS, give declination)	ID	Frequency (CH)	Hours of operation	Position of transmitting antenna coordinates	Elevation of DME transmitting antenna	Remarks
1	2	3	4	5	6	7
KASSOS L (5°E/2024)	KAO	333 kHz	H24	352512.44N 0265449.40E	-	Coverage 25 NM
All Radio Navigation and Landing Aids under responsibility of HASP. See also GEN 2.5						

LGKS AD 2.20 LOCAL TRAFFIC REGULATIONS**2.20.1 Airport regulations**

NIL

2.20.2 Taxiing to and from stands

NIL

2.20.3 Parking area for small aircraft (General aviation)

NIL

2.20.4 Parking area for helicopters

2.20.4.1 An area in the apron which pending on the AD traffic and parking availability, is specified each time by the AD operator.

2.20.5 Apron - taxiing during winter conditions

NIL

2.20.6 Taxiing - limitations

NIL

2.20.7 School and training flights - technical test flights - use of runways

NIL

2.20.8 Helicopter traffic - limitation

NIL

2.20.9 Removal of disabled aircraft from runways

NIL

LGKS AD 2.21 NOISE ABATEMENT PROCEDURES**Part I****2.21.1 Noise abatement procedures for jet aeroplanes irrespective of weight, and for propeller and turboprop aeroplanes with MTOM of or above 11 000 KG**

2.21.1.1 General provisions

NIL

2.21.1.2 Use of the runway system during the day period 0600-2200 (0500-2100)

NIL

2.21.1.3 Use of the runway system during the night period 2200-0600 (2100-0500)

NIL

2.21.1.4 Restrictions

NIL

2.21.1.5 Reporting

NIL

Part II**2.21.2 Noise abatement procedures for propeller and turboprop aeroplanes with MTOM below 11 000 KG**

2.21.2.1 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.2.2 Use of the runway system during the night period 2300-0600 (2200-0500)

NIL

2.21.2.3 Reporting

NIL

Part III

2.21.3 Noise abatement procedures for helicopters

2.21.3.1 General provisions

NIL

2.21.3.2 Use of the runway system during the day period 0600-2300 (0500-2200)

NIL

2.21.3.3 Use of the runway system during the night period 2300-0600 (local time)

NIL

2.21.3.4 Reporting

NIL

LGKS AD 2.22 FLIGHT PROCEDURES

2.22.1 General

2.22.1.1 First 250 M of RWY 27 are visible only from AFIS site in the Terminal building.

2.22.1.2 For AFIS see **AD 1.1.6.2**.

2.22.2 Runway in use

NIL

2.22.3 Procedures for IFR flights within ... TMA

NIL

2.22.4 Radar procedures within ... TMA

NIL

2.22.5 Procedures for VFR flights within IRAKLION TMA KARPATHOS AREA

2.22.5.1 VFR flights entering IRAKLION TMA KARPATHOS AREA shall follow VFR routes and altitudes, unless other clearance is provided by IRAKLION APP.

2.22.6 Procedures for VFR flights within KARPATHOS CTR

2.22.6.1 See relevant VFR routes KARPATHOS AREA chart (**AD 2-LGKP-VFR**).

2.22.7 Standard instrument departure procedure (SID)

NIL

LGKS AD 2.23 ADDITIONAL INFORMATION

2.23.1 Bird concentrations in the vicinity of the airport

2.23.1.1 No significant concentration of birds on and at the vicinity of airport during daylight hours. See also **ENR 5.6**

LGKS AD 2.24 CHARTS RELATED TO AERODROME

Chart name	Date	Page
Aerodrome Chart – ICAO: - KASSOS Airport	07 JUL 05	AD 2-LGKS-ADC
Aircraft Parking/ Docking Chart – ICAO: -	NIL	NIL
Aerodrome Obstacle Chart (AOC) - ICAO, Type A: - RWY 09/27 / LGKS AOC	07 JUL 05	AD 2-LGKS-AOC A-1
Aerodrome Obstacle Chart (AOC) – ICAO, Type B: -	NIL	NIL
Precision Approach Terrain Chart – ICAO: -	NIL	NIL
Instrument Approach Chart (IAC) – ICAO: -	NIL	NIL
Visual Approach Chart (VAC) – ICAO: -	NIL	NIL
Standard Departure Chart - Instrument (SID) – ICAO: -	NIL	NIL
Standard Arrival Chart - Instrument (STAR) – ICAO: -	NIL	NIL
TMA - VFR routes: -	NIL	NIL

LGKS AD 2.25 VISUAL SEGMENT SURFACE (VSS) PENETRATION