

 AD 3.71 MIKONOS / KALO LIVADI**AD 3.71.1 HELIPORT NAME AND INDICATORS**

1. Location Indicator	2. Name	3. Grouping Indicator
NIL	MIKONOS / KALO LIVADI	P/HEL

AD 3.71.2 HELIPORT GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Heliport reference point coordinates and site at heliport	372616N 0252433E, geometric centre of FATO
2	Direction and distance from (city)	At location "Kalo Livadi", Mikonos
3	Elevation/Reference temperature	54 M (177 FT) / NIL
4	Geoid undulation at ELEV PSN	NIL
5	MAG VAR/Annual change	NIL / NIL
6	Heliport Administration, address, telephone, telefax,, AFS	ELIAS SOFIANOS TEL:+30 6944 523723
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	PPR by the owner. Supervised by CAA

AD 3.71.3 OPERATIONAL HOURS

1	Heliport Administration	HX
1 2	Remarks	HX: daily hours O/R

AD 3.71.4 HANDLING SERVICES AND FACILITIES

NIL

AD 3.71.5 PASSENGER FACILITIES

NIL

AD 3.71.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	H1
4	Remarks	NIL

AD 3.71.7 SEASONAL AVAILABILITY - CLEARING

NIL

AD 3.71.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

NIL

AD 3.71.9 MARKINGS AND MARKERS

1	Final approach and take-off markings	Heliport identification (H), TLOF edge, TDZ marking.
2	TWY, air TWY, air transit route markers	NIL
3	Remarks	NIL

AD 3.71.10 HELIPORT OBSTACLES

In Area 2					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

In Area 3					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

AD 3.71.11 METEOROLOGICAL INFORMATION PROVIDED

NIL

AD 3.71.12 HELIPORT DATA

1	Heliport type	Surface level
2	TLOF dimensions	13 M in diameter
3	FATO, GEO bearings	190° / 311° GEO
4	FATO dimensions and SFC type	13 M in diameter, concrete
5	TLOF, SFC and BRG strength	concrete
6	Coordinates of geometric centre TLOF or THR of FATO and geoid undulation	TLOF: 372615.91N 0252432,92E / NIL
7	TLOF/FATO, elevation and slope	TLOF: 54 M (177 FT) / NIL
8	Safety area dimensions	6,5 M width
9	HEL CWY dimensions	NIL
10	Obstacle free sector	NIL
11	Remarks	To be used by helicopters with maximum length 13 M.

AD 3.71.13 DECLARED DISTANCES

NIL

AD 3.71.14 APPROACH AND FATO LIGHTING

2	Type of visual approach slope indicator system	NIL
5	TLOF LGT system characteristics and location	NIL
6	Remarks	NIL

AD 3.71.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Heliport BCN location and characteristics Hours of operation	NIL
2	WDI location and LGT	NORTH – EAST OF FATO / NOT LIGHTED
4	Secondary power supply/switch-over time	NIL
5	Remarks	NIL

AD 3.71.16 ATS AIRSPACE

NIL

AD 3.71.17 ATS COMMUNICATION FACILITIES

NIL

AD 3.71.18 ATS RADIO NAVIGATION AND LANDING AIDS

NIL

AD 3.71.19 LOCAL TRAFFIC REGULATIONS**3.71.19.1 Heliport regulations**

3.19.19.1.1 The heliport will be used exclusively for the needs of the owner as well as for the needs of persons who have obtained the permission of the owner.

AD 3.71.20 NOISE ABATEMENT PROCEDURES**3.71.20.1** NIL**AD 3.71.21 FLIGHT PROCEDURES****3.71.21.1 General**

3.71.21.1.1 Heliport is located within MIKONOS TMA (see **ENR 2.1.5.10**) and within MIKONOS ATZ

3.71.21.1.2 Prior coordination and approval from MIKONOS ATC (tel: +30 2289079004) is required for all local VFR flights

3.71.21.1.3 Prior any helicopter departure or arrival, coordination with LGMK – MIKONOS ATS unit (see **LGMK AD 2.18**) is required. Helicopters operating from the heliport will start up only after having received ATC clearance from MIKONOS TWR

3.71.21.1.4 Heliport can be used only during day time and under VMC conditions

3.71.21.1.5 Helicopter flights to and from the heliport shall be conducted according to AIP Greece ENR 1.2 Visual Flight Rules.

AD 3.71.22 ADDITIONAL INFORMATION**3.71.22.1** NIL**AD 3.71.23 CHARTS RELATED TO THE HELIPORT**

NIL