

AD 3.76 MYKONOS / KALAFATIS**AD 3.76.1 HELIPORT NAME AND INDICATORS**

1. Location Indicator	2. Name	3. Grouping Indicator
NIL	MYKONOS/ KALAFATIS	P/HEL

AD 3.76.2 HELIPORT GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	Heliport reference point coordinates and site at heliport	372637.00N 0252506.00E
2	Direction and distance from (city)	7.7Km East from city
3	Elevation/Reference temperature	66 M / NIL
4	Geoid undulation at ELEV PSN	NIL
5	MAG VAR/Annual change	NIL / NIL
6	Heliport Administration, address, telephone, telefax,, AFS	Duofol Holdings LTD, Palmsol Co LTD, Restmar Co LTD TEL: +30 6944126508 EMAIL: dfour@intrapower.gr
7	Types of traffic permitted (IFR/VFR)	VFR
8	Remarks	PPR by the owner. Supervised by CAA

AD 3.76.3 OPERATIONAL HOURS

1	Heliport Administration	HX
12	Remarks	HX: daily hours O/R

AD 3.76.4 HANDLING SERVICES AND FACILITIES

NIL

AD 3.76.5 PASSENGER FACILITIES

NIL

AD 3.76.6 RESCUE AND FIRE FIGHTING SERVICES

1	AD category for fire fighting	H1
4	Remarks	NIL

AD 3.76.7 SEASONAL AVAILABILITY - CLEARING

NIL

AD 3.76.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

NIL

AD 3.76.9 MARKINGS AND MARKERS

1	Final approach and take-off markings	Heliport identification (H), FATO edge, TLOF edge.
2	TWY, air TWY, air transit route markers	NIL
3	Remarks	NIL

AD 3.76.10 HELIPORT OBSTACLES

In Area 2					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

In Area 3					
OBST ID/ Designation	OBST type	OBST position	ELEV / HGT	Markings/ Type, colour	Remarks
a	b	c	d	e	f
NIL	NIL	NIL	NIL	NIL	NIL

AD 3.76.11 METEOROLOGICAL INFORMATION PROVIDED

NIL

AD 3.76.12 HELIPORT DATA

1	Heliport type	Surface level
2	TLOF dimensions	16.50 M diameter
3	FATO, GEO bearings	147° / 358° GEO
4	FATO dimensions and SFC type	16.50 M diameter, concrete
5	TLOF, SFC and BRG strength	concrete
6	Coordinates of geometric centre TLOF or THR of FATO and geoid undulation	TLOF: 372636.61N 0252506.13E/ NIL
7	TLOF/FATO, elevation and slope	TLOF: 16.50 M / NIL
8	Safety area dimensions	22 M diameter
9	HEL CWY dimensions	NIL
10	Obstacle free sector	NIL
11	Remarks	To be used by helicopters with maximum length 11 M.

AD 3.76.13 DECLARED DISTANCES

NIL

AD 3.76.14 APPROACH AND FATO LIGHTING

2	Type of visual approach slope indicator system	NIL
5	TLOF LGT system characteristics and location	NIL
6	Remarks	NIL

AD 3.76.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	Heliport BCN location and characteristics Hours of operation	NIL
2	WDI location and LGT	East of FATO, not LGTD
4	Secondary power supply/switch-over time	NIL
5	Remarks	NIL

AD 3.76.16 ATS AIRSPACE

NIL

AD 3.76.17 ATS COMMUNICATION FACILITIES

NIL

AD 3.76.18 ATS RADIO NAVIGATION AND LANDING AIDS

NIL

AD 3.76.19 LOCAL TRAFFIC REGULATIONS**3.76.19.1 Heliport regulations**

3.76.19.1.1 The heliport will be used exclusively for the needs of the owner as well as for the needs of persons who have obtained the permission of the owner.

AD 3.76.20 NOISE ABATEMENT PROCEDURES**3.76.20.1** NIL**AD 3.76.21 FLIGHT PROCEDURES****3.76.21.1 General**

3.76.21.1.1 All flights shall be conducted according to AIP Greece Part 2 En Route (ENR) provisions.

3.76.21.1.2 Prior any helicopter departure or arrival, coordination with LGMK ATS unit (see **LG MK AD 2.18**) is required.

3.76.21.1.3 Heliport can be used only during day time and under VMC conditions.

3.76.21.1.4 Helicopter flights to and from the heliport shall be conducted according to AIP Greece **ENR 1.2** Visual Flight Rules.

AD 3.76.22 ADDITIONAL INFORMATION

3.76.22.1 Unmarked electrical overhead wire West of North Approach Surface of Heliport spans from West Inner Edge corner for 100 M outwards. Unmarked electrical overhead wires below North Approach Surface of Heliport run parallel to its Inner Edge, at a distance of 100 M. Caution advised.

AD 3.76.23 CHARTS RELATED TO THE HELIPORT

NIL